



Dasqua



6112-1232/1247/1283/1287/1112/1122

CALIBRATION GAUGE BLOCK SET



CERTIFICATE					
Dasqua					
Product name: Gage blocks		Standard: DIN ISO 3650		Set No: 6112-1232 (32PCS)	
Type: Rect		Material: Steel		Grade: 2	
Nominal Size (mm)	Run out (μm)	Nominal Size (mm)	Run out (μm)	Nominal Size (mm)	Run out (μm)
1.005	+0.32	1.20	+0.20	4	-0.10
1.01	+0.20	1.30	+0.20	5	-0.17
1.02	+0.30	1.40	+0.20	6	-0.10
1.03	+0.10	1.50	+0.20	7	-0.10
1.04	-0.30	1.60	+0.20	8	+0.20
1.05	-0.03	1.70	+0.20	9	-0.17
1.06	-0.20	1.80	+0.20	10	+0.30
1.07	-0.05	1.90	+0.20	20	+0.08
1.08	-0.10	2	+0.20	30	+0.20
1.09	+0.25	3	+0.20	50	-0.19
1.10	+0.25				

Remarks: Standard reference temperature: 68°F (20°C)
Coefficient of thermal expansion: $(11.5 \pm 1.0) \times 10^{-6} / ^\circ\text{C}$

Reported by: David

Description

- High- carbon, high chrome steel provides high hardness and wear resistance
- Strictly made in accordance with DIN ISO 3650
- Made of high quality alloy steel
- Edges are slightly lapped for protection

Unit:mm

Code	Piece/Set	Grade
6112-1232	32	Grade 2
6112-1247	47	Grade 2
6112-1283	83	Grade 2
6112-1287	87	Grade 2
6112-1112	112	Grade 2
6112-1122	122	Grade 2