

DIGITAL 3-POINT PISTOL BORE GAUGE

- Absolute system
- 3V Lithium battery CR2032
- SPC data output
- Built in wireless data transmission (optional)
- Measuring contact points are designed to allow measurements near the bottom of blind holes
- Setting rings for origin point setting
- Display can rotate 90°
- With carbide measuring face

mm
inDIN
863Battery
+
CR2032

Absolute

Data
output

Size till **350** mm
First in the area

Unit:mm

Code	Range	Ring gauge	A	B	D	Accuracy
4600-0001-A	6-8/0.275-0.35"	φ8	55	1	φ5.8	0.004/0.00015"
4600-0002-A	8-10/0.35-0.425"	φ8	55	1.5	φ5.8	0.004/0.00015"
4600-0003-A	10-12/0.425-0.5"	φ12	55	1.5	φ5.8	0.004/0.00015"
4600-0004-A	12-16/0.5-0.65"	φ16	80	0.5	φ11.8	0.004/0.00015"
4600-0005-A	16-20/0.65-0.8"	φ16	80	0.5	φ11.8	0.004/0.00015"
4600-0006-A	20-25/0.8-1.0"	φ25	90	0.5	φ15.8	0.004/0.00015"
4600-0007-A	25-30/1.0-1.2"	φ25	90	0.5	φ15.8	0.004/0.00015"
4600-0008-A	30-40/1.2-1.6"	φ40	105	0.5	φ23.8	0.004/0.00015"
4600-0009-A	40-50/1.6-2.0"	φ40	105	0.5	φ23.8	0.005/0.0002"
4600-0010-A	50-63/2.0-2.5"	φ62	127	0.5	φ23.8	0.005/0.0002"
4600-0011-A	62-75/2.5-3.0"	φ62	127	0.5	φ23.8	0.005/0.0002"
4600-0012-A	75-88/3.0-3.5"	φ87	127	0.5	φ23.8	0.005/0.0002"
4600-0013-A	87-100/3.5-4.0"	φ87	127	0.5	φ23.8	0.005/0.0002"